

Surface Mount Schottky Barrier Rectifier 60V Current 8A


FEATURES AND BENEFITS

- Low power loss, high efficiency operation
- Low forward voltage drop
- Fast switching capability
- High forward surge capability
- Excellent High Temperature Stability

MECHANICAL DATA

- Epoxy : UL94 V-0 rated flame retardant
- Case: TO-277 Package
- Terminals: Matte Tin annealed over copper
- Weight: Approximated 0.129 grams

Primary Characteristic	
I _O	8A
V _{RRM}	60V
I _{FSM}	150A
V _F Typical=2.5A T _J =125°C	0.30V
T _{Jmax}	125°C



Maximum Ratings (Ta=25°C unless otherwise specified)

Characteristics	Symbol	Value	Unit
Peak Repetitive Reverse Voltage	V _{RRM}	60	V
Working Peak Reverse Voltage	V _{RWM}	60	V
DC Blocking Voltage	V _{DC}	60	V
RMS Reverse Voltage	V _{RMS}	42	V
Average Forward Rectified Current (per diode)	I _O	8	Amps
Peak Forward Surge Current, 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	I _{FSM}	150	Amps

Electrical Characteristics (Ta=25°C unless otherwise specified)

Characteristics	Symbol	Typ.	Max.	Unit
Forward Voltage Drop ⁽¹⁾	V _F	0.40	0.44	V
	V _F	0.49	0.53	V
	V _F	0.30	0.34	V
	V _F	0.46	0.50	V
Reverse Current ⁽²⁾	I _R	30	90	µA
	I _R	10	30	mA

Notes (1): Pulse test: 300µs pulse width, 1% duty cycle,

Notes (2): Pulse width ≤40ms

THERMAL CHARACTERISTICS (TA = 25 °C unless otherwise noted)

Characteristics	Symbol	Value	Unit
Typical Thermal Resistance, junction to ambient	R _{θJA}	105	°C/W
Operating Temperature Range (in DC Mode)	T _J	-65 to +125	°C
Storage Temperature Range	T _{STG}	-65 to +150	°C

Notes (3): FR-4 PCB, 2oz copper. Minimum recommended pad layout

RATINGS AND CHARACTERISTICS CURVES

Fig 1. Typical Forward Characteristics




Fig 2. Typical Reverse Characteristics




Fig 3. Typical Forward Current Derating Curve






Fig 4. Non-repetitive Forward Surge Current




Package Outline Dimensions (in millimeters)



SYMBOL	DIMENSIONS		
	MIN	NOM	MAX
A	1.05	1.10	1.15
b1	0.80	0.90	0.99
b2	1.70	1.79	1.88
b3	0.15	0.25	0.35
C	0.20	0.25	0.33
D	4.00	4.20	4.30
D1	3.90	3.98	4.05
D2	2.95	3.05	3.15
E	6.40	6.50	6.60
E1	5.30	5.40	5.45
E2	3.45	3.55	3.65
E3	4.20	4.40	4.60
e	1.84 Typ		
L	0.75	0.85	0.95

LAND PATTERN RECOMMENDATION

Marking Information



SLQ =Product Type Marking Code
 8S60P =Part Number Marking Code
 AABBCCC =Product Tracking Code