

Surface Mount Schottky Barrier Rectifier 60V Current 3A


FEATURES AND BENEFITS

- Low power loss, high efficiency operation
- Low forward voltage drop
- Fast switching capability
- High forward surge capability
- Excellent High Temperature Stability


MECHANICAL DATA

- Epoxy : UL94 V-0 rated flame retardant
- Case: TO-277 Package
- Terminals: Matte Tin annealed over copper
- Weight: Approximated 0.129 grams

Primary Characteristic	
I_O	3A
V_{RRM}	60V
I_{FSM}	100A
V_F Typical=3A $T_J=125^\circ\text{C}$	0.49V
T_{Jmax}	150°C



Top View



Bottom View

Maximum Ratings ($T_a=25^\circ\text{C}$ unless otherwise specified)

Characteristics	Symbol	Value	Unit
Peak Repetitive Reverse Voltage	V_{RRM}	60	V
Working Peak Reverse Voltage	V_{RWM}	60	V
DC Blocking Voltage	V_{DC}	60	V
RMS Reverse Voltage	V_{RMS}	42	V
Average Forward Rectified Current (per diode)	I_O	3	Amps
Peak Forward Surge Current, 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	I_{FSM}	100	Amps

Electrical Characteristics ($T_a=25^\circ\text{C}$ unless otherwise specified)

Characteristics			Symbol	Typ.	Max.	Unit
Forward Voltage Drop ⁽¹⁾	IF=3A	$T_a=25^\circ\text{C}$	V_F	0.53	0.57	V
	IF=6A	$T_a=25^\circ\text{C}$	V_F	0.65	0.69	V
	IF=3A	$T_a=125^\circ\text{C}$	V_F	0.49	0.53	V
	IF=6A	$T_a=125^\circ\text{C}$	V_F	0.60	0.64	V
Reverse Current ⁽²⁾	VR=60V	$T_a=25^\circ\text{C}$	I_R	3	150	μA
	VR=60V	$T_a=125^\circ\text{C}$	I_R	1	3	mA

Notes (1): Pulse test: 300 μs pulse width, 1% duty cycle,

Notes (2): Pulse width $\leq 40\text{ms}$

THERMAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Characteristics	Symbol	Value	Unit
Typical Thermal Resistance, junction to ambient	$R_{\theta JA}$	105	$^\circ\text{C/W}$
Operating Temperature Range (in DC Mode)	T_J	-65 to +150	$^\circ\text{C}$
Storage Temperature Range	T_{STG}	-65 to +150	$^\circ\text{C}$

Notes (3): FR-4 PCB, 2oz copper. Minimum recommended pad layout

RATINGS AND CHARACTERISTICS CURVES

Fig 1. Typical Forward Characteristics




Fig 2. Typical Reverse Characteristics




Fig 3. Typical Forward Current Derating Curve







Fig 4. Non-repetitive Forward Surge Current



Package Outline Dimensions (in millimeters)




SYMBOL	DIMENSIONS		
	MIN	NOM	MAX
A	1.05	1.10	1.15
b1	0.80	0.90	0.99
b2	1.70	1.79	1.88
b3	0.15	0.25	0.35
C	0.20	0.25	0.33
D	4.00	4.20	4.30
D1	3.90	3.98	4.05
D2	2.95	3.05	3.15
E	6.40	6.50	6.60
E1	5.30	5.40	5.45
E2	3.45	3.55	3.65
E3	4.20	4.40	4.60
e	1.84 Typ		
L	0.75	0.85	0.95



LAND PATTERN RECOMMENDATION

Marking Information



SAT =Product Type Marking Code
 360P =Part Number Marking Code
 AABBCCC =Product Tracking Code