

Dual Common-Cathode Ultra Low VF Schottky Rectifier


FEATURES AND BENEFITS

- Low power loss, high efficiency operation
- Low forward voltage drop
- Fast switching capability
- High forward surge capability
- Excellent High Temperature Stability
- Green Product Compliant (Pb<100ppm)

MECHANICAL DATA

- Epoxy : UL94 V-0 rated flame retardant
- Case: TO-220AB / ITO-220AB Package
- Terminals: Matte Tin annealed over copper
- Weight: Approximated 2.03 grams

Primary Characteristic	
I_O	2X15A
V_{RRM}	120V
I_{FSM}	180A
V_F Typical=1.5A $T_J=125^\circ\text{C}$	0.34V
T_{Jmax}	175°C







Maximum Ratings (Ta=25°C unless otherwise specified)						
Characteristics			Symbol	Value		Unit
Peak Repetitive Reverse Voltage			V _{RRM}	120		V
Working Peak Reverse Voltage			V _{RWM}	120		V
DC Blocking Voltage			V _{DC}	120		V
RMS Reverse Voltage			V _{RMS}	84		V
Average Forward Rectified Current (per diode)			I _O	15		Amps
Peak Forward Surge Current, 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)			I _{FSM}	180		Amps
Electrical Characteristics (Ta=25°C unless otherwise specified)						
Characteristics			Symbol	Typ.	Max.	Unit
Forward Voltage Drop	IF=1.5A	Ta=25°C	V _F	0.43	0.47	V
	IF=15A	Ta=25°C	V _F	0.77	0.81	V
	IF=1.5A	Ta=125°C	V _F	0.34	0.38	V
	IF=15A	Ta=125°C	V _F	0.54	0.58	V
Reverse Current	VR=120V	Ta=25°C	I _R	10	30	µA
	VR=120V	Ta=125°C	I _R	5	15	mA
THERMAL CHARACTERISTICS (TA = 25 °C unless otherwise noted)						
Characteristics			Symbol	Value		Unit
Typical Thermal Resistance, junction to case		TO-220AB	R _{θJC}	2.8		°C/W
Typical Thermal Resistance, junction to case		ITO-220AB	R _{θJC}	4.0		°C/W
Operating Temperature Range (in DC Mode)			T _J	-65 to +175		°C
Storage Temperature Range			T _{STG}	-65 to +150		°C

Notes (1): Pulse test: 300 μs pulse width, 1% duty cycle.

Notes (2): Pulse width $\leq 40\text{ms}$

Notes (3): FR-4 PCB, 2oz copper. Minimum recommended pad layout

RATINGS AND CHARACTERISTICS CURVES



Package Outline Dimensions (in millimeters)

ITO-220				
SYMBOL	Dimensions			
	Millimeters		Inches	
	Min	Max	Min	Max
A	4.60	4.80	0.18	0.19
b	0.70	0.91	0.03	0.04
b1	1.20	1.47	0.05	0.06
b2	1.10	1.30	0.04	0.05
C	0.45	0.63	0.02	0.02
D	15.80	15.97	0.62	0.63
e	2.54			
E	10.00	10.10	0.39	0.40
F	2.44	2.54	0.10	0.10
G	6.50	6.70	0.26	0.26
L	12.90	13.10	0.51	0.52
L1	3.13	3.23	0.12	0.13
Q	2.65	2.75	0.10	0.11
Q1	3.20	3.30	0.13	0.13
ψ	3.08	3.18	0.12	0.13




Diagram illustrating the ITO-220 package outline dimensions. The package is shown from top, side, and bottom views. Key dimensions include: A (height), b (lead width), b1 (lead width at base), b2 (lead width at base), C (lead thickness), D (package width), e (pitch), E (package length), F (lead length), G (lead length), L (lead length), L1 (lead length), Q (lead length), Q1 (lead length), and ψ (lead length). The bottom view shows the package with three leads and a central pad.

TO-220				
SYMBOL	Dimensions			
	Millimeters		Inches	
	Min	Max	Min	Max
A	3.56	4.82	0.14	0.19
A1	0.51	1.39	0.02	0.05
A2	2.04	2.92	0.08	0.11
b	0.39	1.01	0.02	0.04
b1	1.15	1.82	0.05	0.07
b2	1.15	1.77	0.05	0.07
c	0.04	0.50	0.00	0.02
D	14.22	16.51	0.56	0.65
D1	8.39	9.01	0.33	0.35
D2	11.45	12.87	0.45	0.51
E	9.66	10.66	0.38	0.42
E1	6.86	8.89	0.27	0.35
e	2.54BSC		2.54BSC	
e1	5.08BSC		5.08BSC	
H1	5.85	6.85	0.23	0.27
L	12.70	14.73	0.50	0.58
L1	-	6.35	-	0.25
L2	15.80	16.20	0.62	0.64
ψP	3.54	4.08	0.14	0.16
Q	2.54	3.42	0.10	0.13





Diagram illustrating the TO-220 package outline dimensions. The package is shown from top, side, and bottom views. Key dimensions include: A (height), A1 (lead width), A2 (lead width), b (lead width), b1 (lead width at base), b2 (lead width at base), c (lead thickness), D (package width), D1 (package width), D2 (package width), E (package length), E1 (package length), e (pitch), e1 (pitch), H1 (lead length), L (lead length), L1 (lead length), L2 (lead length), ψP (lead length), and Q (lead length). The bottom view shows the package with three leads and a central pad.

Marking Information



mO-SEMI =Series Name
SLT30L120 =Part Number Marking Code
AABBCCC =Product Tracking Code
*FCT=ITO-220 =Dual ITO-220
*CT=TO-220 =Dual TO-220